

Flexible waterproof LED strip

AKTOFlexLine



- Samsung LEDs.
- Minor voltage drop – 2 oz PCB.
- High color rendering index CRI>80.



- Low color temperature tolerances (MacAdam 3).
- Full range of colors (6500K, 4000K, 3000K, 2700K, 2000K).
- Easy installation (e.g. double-sided adhesive tape).



- Extensive use of options (e.g. for furniture, architectural, accent lighting).
- Long LEDs life time: >50 000 h.
- 5-year warranty.
- Made in Europe.

EXTENSIVE USE OF OPTIONS:

Accent lighting



Residential use



Commercial lighting projects



Outdoor lighting



Shop equipment



Furniture manufacturing



Lighting fixtures manufacturing



TECHNICAL DATA



Model	AFL-60U144MHT-XW				
Dimensions, mm	1000x12x5				
Current, A	~1.2				
Voltage, V	12 DC				
Power, W/m	~14.4				
LED quantity, pcs	60				
Color	Cold white	Neutral white	Warm white	Warm white	Amber white
Color temperature (CCT)	6500K (-CW)	4000K (-NW)	3000K (-WW)	2700K (-WWW)	2000K (-20)
Luminous flux, Lm	1385	1385	1299	1270	1460
Color rendering index (CRI)	>80				
Light angle	120°				
Working temperature (Tc point)	-25°- +65°				
Cutting step, mm	50				
Ingress protection	IP67				
Package	5 meters				

TECHNICAL DRAWING (mm)

