


## Round LED module CRI>80



- Samsung LEDs.
- Low color temperature tolerances (MacAdam 3).
- Wide range of colors (5000K, 4000K, 3000K).
- High color rendering index CRI >80.
- Ideal for panel lights.
- Perfectly uniform light, even if several LED modules are used together in one line.
- Complies with Zhaga standard.
- Easy installation.
- Long life time: >50 000 hours.
- 5-year warranty.

### EXTENSIVE USE OF OPTIONS:

Lighting fixtures  
manufacturing



Residential  
use



Commercial  
lighting projects



Outdoor  
lighting




### TECHNICAL DATA



Model	AM-D164-6p14sRA-XW		
Dimensions, mm	D164x4.3		
Typical current, mA	600		
Typical voltage, V	38.3		
Power, W	23.0		
LED quantity, pcs	84		
Color	Pure white	Neutral white	Warm white
Color temperature	5000K (-PW)	4000K (-NW)	3000K (-WW)
Luminous flux, Lm	4327	4272	4080
Luminous efficacy, Lm/W	188.2	185.9	177.5
Color rendering index (CRI)	>80		
Operating temperature	-40°C – +85°C		
Temperature at Tc point	+45°C		
Light angle	120°		
MAX current, mA	1200		
MAX luminous flux, Lm	8157	8053	7692
Connection	2 x 1 pole connector. For 0.15-0.35 mm <sup>2</sup> wires		

### TECHNICAL DRAWING (mm)



AKTO – LED MODULES, STRIPS & EMS  
Mituvos str. 4, LT-50130, Kaunas, Lithuania

Email: donatas@aktoled.com  
Mobile: +370 618 84101

www.aktoled.com

