AKTO
LED MODULES, STRIPS & EMS

Tunable white LED module CRI>90

- Samsung LEDs.
- Low color temperature tolerances (MacAdam 3).
- Wide range of colors (6500K, 4000K, 3000K, 2700K).
- High color rendering index CRI >90.
- Ideal for linear and panel lights.
- Perfectly uniform light, even if several LED modules are used together in one line.
- Complies with Zhaga standard.
- Easy installation.
- Long life time: >50 000 hours.
- 5-year warranty.

EXTENSIVE USE OF OPTIONS:

Lighting fixtures manufacturing

Residential use

Commercial lighting projects

Outdoor lighting

TECHNICAL DATA

Model	AM-L525W239-8p16sRB-TW	
Dimensions, mm	525x239x5.6	
Typical current, mA	800+800	
Typical voltage, V	43.84	
Power, W	70.14	
LED quantity, pcs	256	
Color	Cold white	Warm white
Color temperature	6500K **(-CW)**	2700K **(-WWW)**
Luminous flux, Lm	5508	5132
Luminous efficacy, Lm/W	157.3	146.5
Color rendering index (CRI)	>90	
Operating temperature	-40°C – +85°C	
Temperature at Tc point	+45°C	
Light angle	120°	
MAX current, mA	1600+1600	
MAX luminous flux, Lm	10384	9676
Connection	2 x 1 pole connector. For 0.15-0.35 mm² wires	

NOTE: Values with equal (50% / 50%) channel balance

TECHNICAL DRAWING (mm)





AKTO – LED MODULES, STRIPS & EMS
Mituvos str. 4, LT-50130, Kaunas, Lithuania

Email: donatas@aktoled.com
Mobile: +370 618 84101

www.aktoled.com